

35 Ton Fixed Height Tripod Jack

Model 8826



The Model 8826 Fixed Height Tripod Jack is a 35 ton capacity, single stage hydraulic jack designed primarily for use in aircraft maintenance. It consists of a tripod structure, hydraulic cylinder/reservoir assembly, adjustable hand pump and swivel casters.

The jack leg pads are raised off the ground by spring loaded casters. The casters will retract and the pads rest on the ground when a load is applied to the jack.

Model 8826 is built to withstand harsh environmental conditions, rugged use and to provide many years of continuous service. Our customers are guaranteed a quality product with each purchase and are assured of our continued product support whenever and wherever the need arises.

Standard Features:



- Manual hand pump with high, medium and low pressure operating positions
- Heavy duty tow handle and swivel casters with swivel locks for improved towing
- Secondary cylinder seal for protection against contaminants and to prolong life of primary seal
- Rain hat (covers jack upper head)
- Hard chrome plated cylinder bore
- All unpainted parts are plated to resist corrosion
- Skydrol resistant paint (safety yellow)
- Factory proof load @ 150% of rated capacity
- Three year standard warranty
- Shipment on domestic skid

Optional Features:

- Air operated hydraulic pump
- Load gauge for load indication (reads tons/psig)
- Adjustable swivel feet with level for leveling jack
- Export crating
- Customer specified paint color

35 Ton Fixed Height Tripod Jack

Model 8826



For more information contact: sales@malabar.com

35 Ton Fixed Height Tripod Jack

Model 8826

Specifications:

Rated Capacity	35 tons (31.8 m. tons)
Side Load	15% of vertical load
Roll Under Height	61.5 inches (1562 mm)
Low Height	60 inches (1524 mm)
Hydraulic Lift	44 inches (1118 mm)
Extension Screw	16 inches (406 mm)
Total Extended Height	120 inches (3048 mm)
Oil Pressure at Rated Capacity	2260 psig (159 kg/sq cm)
Safety Pop-off Valve set at:	38.5 tons (34.9 m. tons)
Proof Load	52.5 tons (47.6 m. tons)
Reservoir Capacity	6.1 gallons (23.1 liters)
Hydraulic Fluid	MIL-PRF-5606 or equivalent
Maximum Towing Speed	5 mph (8 km/h)
Approximate Jack Net Weight	1550 lbs (703 kg)

Model 8826 Typical Aircraft Applications:

Wing	Aft Fuselage
BAE146, B727, B737, DC9, ERJ190-E2, F100, MD80, MD90	B727

Optional Equipment Codes:

(Specify with order)

- AP: Air Operated Hydraulic Pump
- GA: Load Gauge
- AF: Adjustable Swivel Foot
- SPC: Special Paint Color (yellow is standard)
- 8826PK: Repair Kit

Packaging Codes & Options:

(Specify with order)

- : Domestic Skid – Jack Set-up
- KD: Domestic Skid – Jack Knocked Down (Additional Cost)
- EC: Export Crate – Jack Set-up (Additional Cost)
- ECKD: Export Crate – Jack Knocked Down (Additional Cost)

35 Ton Fixed Height Tripod Jack

Model 8826

Shipping Data:

NOTE: Unless otherwise specified, Model 8826 jack is shipped on a wood skid in the set-up condition. Refer to Malabar Tripod Jack Shipping Supplement for additional packaging information.

Packaging Code	Length inches (mm)	Width inches (mm)	Height inches (mm)	Weight lbs (kg)
-	77 (1956)	66 (1676)	67 (1702)	1800 (816)
KD	78 (1981)	40 (1016)	42 (1067)	1800 (816)
EC	79 (2007)	71 (1803)	70 (1778)	2050 (930)
ECKD	80 (2032)	45 (1143)	45 (1143)	2100 (953)